

TECHNICAL INFORMATION BULLETIN

MAGNETIC LINEAR BALLAST

RAPID START T12

ORDERING INFORMATION


Order code: 10169
 Description: BM130/40SRS120/TP/STD GLB
 Internal code: 17A1074E
 UPC: 69549101692

GENERAL INFORMATION

Ballast type: Energy efficient magnetic
 Starting method: Rapid Start
 Lamp connection: Series
 Input voltage: 120V
 OCV: 220V
 Frequency: 60HZ
 Class: P
 Type: 1 outdoor
 Sound rated: A
 Does not contain PCB's

Lamp type	Number of lamps	Rated lamp watts	Min. start temp. (°F / °C)	Input watts (W)	Input current (A)	Ballast factor	B.E.F.	Power factor	THD %	Lamp crest factor
F40T12	1	40	50/10	50	0.43	0.95	1.900	0.98	8	1.6
F40T12/ES	1	34	60/16	44	0.38	0.91	2.068	0.97	12	1.8
F40T12/U	1	40	50/10	50	0.43	0.94	1.880	0.98	9	1.6
F40T12/U/ES	1	34	60/16	43	0.36	0.91	2.115	0.99	14	1.8
F40T10	1	40	50/10	50	0.42	0.95	1.900	0.99	9	1.6
F30T12	1	30	50/10	42	0.35	0.97	2.305	0.99	12	1.7
F30T12/ES	1	25	60/16	38	0.32	0.93	2.445	0.99	16	1.8

WIRING DIAGRAM




TECHNICAL INFORMATION BULLETIN

MAGNETIC LINEAR BALLAST

RAPID START T12

BALLAST FEATURES						
Units	M1	M2	M3	W	L	H
INCHES	1.687	8.906	8.344	2.375	9.5	1.5
TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
mm	43	226	212	60	241	38
TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30

LEAD LENGTHS				
	Black	White	Red	Blue
INCHES	22	22	26	36
TOL(+/-)	3/8	3/8	3/8	3/8
mm	559	559	600	914
TOL(+/-)	10	10	10	10



WARRANTY:

Ballast warranty of 2 years for electromagnetic ballasts. Ballast warranty of 3 years for energy saving electromagnetic ballasts. For more information visit our website.



Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



www.standardpro.com