

ORDERING INFORMATION

Order code: 10600
 Description: F14T5/30K/8/PS/G5/STD
 UPC: 69549106000
 Case quantity: 25




Nominal length : 22 in. (559 mm) Dia. : 5/8 in. (16 mm)

PERFORMANCE DATA


Shape: T5
 Base: G5 (Min Bipin)
 Starting method: Program Start (PS)
 Wattage (W): 14
 Colour temperature (K): 3 000
 CRI: 85
 Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 24 000
 Based on a 12 hour start 30 000
 Initial lumens (lm): 1 350
 Mean lumens (lm): 1 280
 Nominal efficiency (lm/W): 96
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



A Max Base face to base face	B Min / B Max Base face to end of opposite face pin	C Max End of base pin to the end of opposite end
21.61 in. 549.0 mm	21.79 in./21.89 in. 553.7 mm/556.1 mm	22.17 in. 563.2 mm

SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T5 ballast.

