

ORDERING INFORMATION

Order code: 10248
 Description: F80T5/41K/8/HO/PS/G5/STD
 UPC: 69549102484
 Case quantity: 25




Nominal length : 58 in. (1 473 mm) Dia. : 5/8 in. (16 mm)

PERFORMANCE DATA


Shape: T5
 Base: G5 (Min Bipin)
 Starting method: Program Start (PS)
 Wattage (W): 80
 Colour temperature (K): 4 100
 CRI: 85
 Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 24 000
 Based on a 12 hour start 30 000
 Initial lumens (lm): 7 000
 Mean lumens (lm): 6 650
 Nominal efficiency (lm/W): 88
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



A Max Base face to base face	B Min / B Max Base face to end of opposite face pin	C Max End of base pin to the end of opposite end
57.04 in. 1 449.0 mm	57.23 in./57.32 in. 1 453.7 mm/1 456.1 mm	57.60 in. 1 463.2 mm

SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T5 High Output ballast.

