

ORDERING INFORMATION

Order code: 58698
 Description: FB31T8/35K/8/U1/PH/G13/STD
 UPC: 69549586987
 Case quantity: 20




Nominal length : 22 ½ in. (572 mm) Dia. : 1 in. (26 mm)

PERFORMANCE DATA


Shape: T8
 Base: G13 (Med Bipin)
 Starting method: Rapid Start (RS)
 Wattage (W): 31
 Colour temperature (K): 3 500
 CRI: 82
 Rated life on IS¹ ballast: 24 000
 Based on a 3 hour start
 Initial lumens (lm): 2 750
 Mean lumens (lm): 2 610
 Nominal efficiency (lm/W): 89
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



A Max	B Max	C Max
Overall length	Base face to top of lamp	Leg spacing Center to center
23 in. 584.2 mm	22.6 in. 574.04 mm	1 in. 26 mm

SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T8 U-Bent 800 series ballast.



E Means this bulb meets federal minimum efficiency standards.