



Features

- Metal halide lamps offer long life, high lumen output, and energy efficiency
- Available in both pulse start and traditional metal halide
- Offered in different wattages to accommodate different applications

Applications

- Security lighting
- Parking garages
- Warehouses

BD17



Dia. = 2 1/8 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/4 in. (86 mm)

BD17



Dia. = 2 1/8 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/4 in. (86 mm)

EDX17



Dia. = 2 1/8 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/4 in. (86 mm)

ED28



Dia. = 3 17/32 in. (90 mm)
MOL = 8 3/8 in. (211 mm)
LCL = 5 in. (127 mm)

ED37



Dia. = 4 23/32 in. (120 mm)
MOL = 11 1/2 in. (292 mm)
LCL = 7 in. (178 mm)

PULSE START

Order code	Description	Watts (W)	Base	Shape	Colour temp. (K)	ANSI code	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty	Figure
58514	MH70W/C/U/PS/ELUME	70	E26	BD17	3700	M98/E	70	15 000	5 300	3 400	U	Coated	Enclosed	24	B
58508	MH70W/U/PS/ELUME	70	E26	BD17	4000	M98/E	65	15 000	5 600	3 600	U	Clear	Enclosed	24	A
58517	MH100W/C/U/PS/ELUME	100	E26	BD17	3700	M90/E	70	15 000	8 500	5 500	U	Coated	Enclosed	24	B
58522	MH100W/U/PS/ELUME	100	E26	BD17	4000	M90/E	65	15 000	9 000	5 900	U	Clear	Enclosed	24	A
58510	MP100W/U/UVS/PS/ELUME	100	E26	EDX17	4000	M90/O	65	15 000	8 500	5 500	U	Clear	Open	24	C
58511	MH150W/U/PS/740/ELUME	150	E26	BD17	4000	M102/E	65	15 000	14 000	10 500	U	Clear	Enclosed	24	A
58521	MP150/U/UVS/PS/740/ELUME	150	E26	EDX17	4000	M102/O	65	15 000	13 300	10 000	U	Clear	Open	24	C

TRADITIONAL

Order code	Description	Watts (W)	Base	Shape	Colour temp. (K)	ANSI code	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty	Figure
58516	MH175W/U/MED/ELUME	175	E26	BD17	4000	M57/E	65	10 000	14 000	9 100	U	Clear	Enclosed	24	A
58509	MH175W/U/ELUME	175	E39	ED28	4000	M57/E	65	10 000	14 000	9 100	U	Clear	Enclosed	12	D
58503	MH250W/U/ELUME	250	E39	ED28	4000	M58/E	65	10 000	21 000	13 700	U	Clear	Enclosed	12	D
58518	MH400W/U/ELUME	400	E39	ED37	4000	M59/E	65	20 000	36 000	23 000	U	Clear	Enclosed	6	E