



G9 lamps are available in 2 lengths, to suit most of the new fixture designs.

Features

- Ceramic and glass bases available
- UV Stop Quartz
- Improved filament support using glass pinch technology (which minimizes deformation)
- Do not require transformers

Benefits

- Safe for use in open fixtures
(Patented integral safety fuses)
- Line voltage application



JC-G4



JCD-GY6.35



JD-G9
Ceramic base



JD-G9
Glass Pinch



JD-E11



JDDC-BA15d



Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour/ Finish	Average life (hrs)	Initial lumens (lm)	MOL (in.) (mm)		Case qty
BA9s											
15537	H5T2.5/BA9S/12V	64111	5	BA9s	12	Clear	-	80	31.00	10	200
15666	HT3.25 12V 20W BA9s #64115	-	20	BA9s	12	Clear	200	340	1.30	33	50
JC Bipin											
58283	H5/JC/CL/2M/G4/12V	-	5	G4	12	Clear	2000	50	11.85	301	50
58790	H5JC/CL/4M/G4/12V	-	5	G4	12	Clear	4000	60	1.30	33	40
51129	H10JC/CL/2M/G4/12V/STD	-	10	G4	12	Clear	2000	130	1.30	33	1000
51130	H20JC/CL/2M/G4/12V/STD	64440	20	G4	12	Clear	2000	300	1.30	33	1000
50902	H50JC/CL/4M/GY6.35/12V/STD	-	50	GY6.35	12	Clear	4000	900	1.73	44	1000
JCD Bipin											
55055	H20JCD/CL/2M/G8/120V/STD	-	20	G8	120	Clear	2000	380	1.81	46	1000
51045	H20JCD/CL/2M/GY6.35/120V/STD	-	20	GY6.35	120	Clear	2000	180	2.17	55	1000
11266	H25JCD/CL/2M/GY8/120V	-	25	GY8	120	Clear	2000	420	1.88	48	1000
10253	H35JCD/CL/2M/G8/120V/STD	-	35	G8	120	Clear	2000	380	1.81	46	1000
50879	H35JCD/CL/2M/GY6.35/120V/STD	-	35	GY6.35	120	Clear	2000	380	2.09	53	1000
50878	H50JCD/CL/2M/GY6.35/120V/STD	-	50	GY6.35	120	Clear	2000	600	2.09	53	1000
10368	H50JCD/CL/2M/G8/120V/STD	-	50	G8	120	Clear	2000	600	1.81	46	1000
10317	H75JCD/CL/2M/GY6.35/120V/STD	-	75	GY6.35	120	Clear	2000	1050	1.93	49	1000
11267	H75JCD/CL/2M/GY8/120V	-	75	GY8	120	Clear	2000	1300	1.88	48	1000
11265	H100JCD/CL/2M/GY8/120V	-	100	GY8	120	Clear	2000	1900	1.88	48	1000
50877	H100JCD/CL/2M/GY6.35/120V/STD	-	100	GY6.35	120	Clear	2000	1500	2.76	70	1000

Order code	Description	Watts (W)	Base	Volts (V)	Colour/ Finish	Average life (hrs)	Initial lumens (lm)	M O L (in.) (mm)	Case qty
JD (G9)									
58260*	H25JD/42mm/CL/2M/G9/130V/STD	25	G9	130	Clear	2 000	255	1.65 42	1 000
58257*	H35JD/42mm/F/2M/G9/130V/STD	35	G9	130	Frost	2 000	380	1.65 42	1 000
57259*	H40JD/42MM/CL/2M/G9/130V/STD	40	G9	130	Clear	2 000	480	1.65 42	1 000
57256*	H40JD/42MM/F/2M/G9/130V/STD	40	G9	130	Frost	2 000	480	1.65 42	1 000
57255*	H50JD/42MM/CL/2M/G9/130V/STD	50	G9	130	Clear	2 000	600	1.65 42	1 000
57261*	H50JD/42MM/F/2M/G9/130V/STD	50	G9	130	Frost	2 000	600	1.65 42	1 000
57258*	H60JD/42MM/CL/2M/G9/130V/STD	60	G9	130	Clear	2 000	800	1.65 42	1 000
55057*	H25JD/56MM/CL/2M/G9/120V/STD	25	G9	120	Clear	2 000	255	2.20 56	1 000
55058*	H40JD/56MM/CL/2M/G9/120V/STD	40	G9	120	Clear	2 000	480	2.20 56	1 000
57253*	H40JD/56MM/F/2M/G9/120V/STD	40	G9	120	Frost	2 000	480	2.20 56	1 000
11247*	H50JD/56MM/CL/2M/G9/120V/STD	50	G9	120	Clear	2 000	600	2.20 56	1 000
15646*	H50JD/56MM/F/2M/G9/120V/STD	50	G9	120	Frost	2 000	600	2.20 56	1 000
55059*	H60JD/56MM/CL/2M/G9/120V/STD	60	G9	120	Clear	2 000	800	2.20 56	1 000
57260*	H60JD/42MM/F/2M/G9/130V/STD	60	G9	130	Frost	2 000	800	1.65 42	1 000
58258*	H75JD/42mm/CL/2M/G9/130V/STD	75	G9	130	Clear	2 000	1 050	1.65 42	1 000
57257*	H60JD/56MM/F/2M/G9/120V/STD	60	G9	120	Frost	2 000	800	2.20 56	1 000
55060*	H75JD/56MM/CL/2M/G9/120V/STD	75	G9	120	Clear	2 000	1 050	2.20 56	1 000
JD (Mini can base line voltage)									
55028	H50T3/CL/2M/E11/130V/STD	50	E11	130	Clear	2 000	1 120	2.48 63	500
50880	H75T3/CL/2M/E11/130V/STD	75	E11	130	Clear	2 000	1 350	2.48 63	50
50951	H150T3/CL/2M/E11/130V/STD	150	E11	130	Clear	2 000	3 000	2.83 72	50
50882	H100T3/CL/2M/E11/130V/STD	100	E11	130	Clear	2 000	1 800	2.99 76	50
50884	H250T3/CL/2M/E11/130V/STD	250	E11	130	Clear	2 000	3 000	3.19 81	50
JD (DC base line voltage)									
50881	H75T3/CL/2M/BA15D/130V/STD	75	BA15d	130	Clear	2 000	1 120	2.24 57	50
50950	H100T3/CL/2M/BA15D/130V/STD	100	BA15d	130	Clear	2 000	1 800	2.56 65	50
50883	H150T3/CL/2M/BA15D/130V/STD	150	BA15d	130	Clear	2 000	3 000	2.56 65	50
50885	H250T3/CL/2M/BA15D/130V/STD	250	BA15d	130	Clear	2 000	4 800	2.95 75	50
JD (Xenon)									
15439	X20T3/3M/KX/BA15D/120V	20	BA15d	120	Clear	3 000	200	2.24 57	50
15440	X20T3/3M/KX/E11/120V	20	E11	120	Clear	3 000	200	2.32 59	50
15443	X20T3/F/3M/KX/E11/120V	20	E11	120	Frost	3 000	200	2.32 59	50
15438	X20T3/3M/KX/E12/120V	20	E12	120	Clear	3 000	200	2.44 62	50
15452	X40T3/F/3M/KX/BA15D/120V	40	BA15d	120	Clear	3 000	560	2.24 57	50
15453	X40T3/3M/KX/E11/120V	40	E11	120	Clear	3 000	560	2.32 59	50
15451	X40T3/3M/KX/E12/120V	40	E12	120	Clear	3 000	560	2.44 62	50
15455	X40T3/F/3M/KX/E12/120V	40	E12	120	Frost	3 000	560	2.44 62	50
15457	X40T3/F/3M/KX/120V	40	E26	120	Frost	3 000	560	2.75 70	50
15465	X60T3/3M/KX/BA15D/120V	60	BA15d	120	Clear	3 000	960	2.24 57	50
15469	X60T3/F/3M/KX/BA15D/120V	60	BA15d	120	Frost	3 000	960	2.24 57	50
11212	X60T3/F/3M/KX/E11/120V	60	E11	120	Frost	3 000	960	2.32 59	50
15466	X60T3/3M/KX/E11/120V	60	E11	120	Clear	3 000	960	2.32 59	50
15468	X60T3/F/3M/KX/E12/120V	60	E12	120	Frost	3 000	960	2.44 62	50
15464	X60T3/3M/KX/E12/120V	60	E12	120	Clear	3 000	960	2.44 62	50
15467	X60T3/3M/KX/120V	60	E26	120	Clear	3 000	960	2.75 70	50
15470	X60T3/F/3M/KX/120V	60	E26	120	Frost	3 000	960	2.75 70	50