



The **ECO PAR Series** provides a high quality, crisp white light. These lamps offer the same performance as traditional halogen PAR lamps while saving up to 30% in energy. With a defined directional beam, the lamps of the ECO PAR Series will add depth and texture to your decor.

PAR20



PAR30



PAR30LN



PAR38



Order code	Description	Watts (W)	Base	Volts (V)	Reflector Finish	Average life (hours)	Initial lumens (lm)	Operating burn position	Beam angle (°C)	Beam spread	CBCP (cd)	Incan. equivalent (W)	Case qty
PAR20													
MOL : 3 1/2 in. (79 mm) Dia. : 2 1/2 in. (63 mm)													
63797	H35/PAR20/ECO/NFL/120V/STD	35	E26	120	Aluminum	2 000	500	Universal	25	Narrow Flood	850	50	15
PAR30													
MOL : 3 1/2 in. (90 mm) Dia. : 3 1/2 in. (95 mm)													
63798	H35/PAR30/ECO/FL/120V/STD	35	E26	120	Silver	2 000	500	Universal	30	Flood	900	50	15
¹ 63799	H60/PAR30/ECO/FL/120V/STD	60	E26	120	Silver	1 500	1 070	Universal	30	Flood	1 100	75	15
PAR30LN													
MOL : 4 1/8 in. (119 mm) Dia. : 3 1/2 in. (95 mm)													
63800	H35/PAR30LN/ECO/FL/120V/STD	35	E26	120	Silver	2 000	500	Universal	30	Flood	900	50	15
¹ 63801	H60/PAR30LN/ECO/FL/120V/STD	60	E26	120	Silver	1 500	1 070	Universal	30	Flood	1 100	75	15
PAR38													
MOL : 5 1/8 in. (132 mm) Dia. : 4 1/8 in. (104 mm)													
¹ 63802	H60/PAR38/ECO/FL/120V/STD	60	E26	120	Silver	1 500	1 070	Universal	30	Flood	1 100	75	15
¹ 63803	H70/PAR38/ECO/FL/120V/STD	70	E26	120	Silver	1 500	1 301	Universal	30	Flood	2 000	90	15

*Not suitable for use in damp locations or outdoors when exposed to weather.
¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.*



Energy Saving PAR Lamps