

MR16 (GX5.3)



PAR20



PAR30



PAR38



Order code	Description	Watts (W)	Base	Volts (V)	Colour/Finish	Beam angle (°)	Beam spread	Average life (hrs)	Case qty
PAR20									
MOL : 3 9/32 in. (83 mm) Dia. : 2.5 in. (63.5 mm)									
55001*	H35PAR20/NFL/Y/2M/130V/STD	35	E26	130	Yellow	30	Narrow Flood	2 000	120
55002*	H35PAR20/NFL/G/2M/130V/STD	35	E26	130	Green	30	Narrow Flood	2 000	120
55004*	H35PAR20/NFL/B/2M/130V/STD	35	E26	130	Blue	30	Narrow Flood	2 000	120
PAR30									
MOL : 3 23/32 in. (93 mm) Dia. : 3 3/4 in. (95 mm)									
55005*	H50PAR30/FL/B/2M/130V/STD	50	E26	130	Blue	30	Flood	2 000	90
55006*	H50PAR30/FL/R/2M/130V/STD	50	E26	130	Red	30	Flood	2 000	90
55007*	H50PAR30/FL/G/2M/130V/STD	50	E26	130	Green	30	Flood	2 000	90
55008*	H50PAR30/FL/Y/2M/130V/STD	50	E26	130	Yellow	30	Flood	2 000	90
PAR38									
MOL : 5 9/16 in. (135 mm) Dia. : 4 3/4 in. (121 mm)									
51181*	H90PAR38/FL/B/2M/MS/130V/STD	90	E26SKT	130	Blue	30	Flood	2 000	15
51182*	H90PAR38/FL/G/2M/MS/130V/STD	90	E26SKT	130	Green	30	Flood	2 000	15
51183*	H90PAR38/FL/R/2M/MS/130V/STD	90	E26SKT	130	Red	30	Flood	2 000	15
51184*	H90PAR38/FL/Y/2M/MS/130V/STD	90	E26SKT	130	Yellow	30	Flood	2 000	15
MR16									
MOL : 1 25/32 in. (45 mm) Dia. : 2 in. (51 mm)									
55063	H50MR16/FL/BLUE/CG/4M/GX5.3/12V/STD	50	GX5.3	12	Blue	38	Flood	4 000	200
55064	H50MR16/FL/G/CG/4M/GX5.3/12V/STD	50	GX5.3	12	Green	38	Flood	4 000	200
55066	H50MR16/FL/R/CG/4M/GX5.3/12V/STD	50	GX5.3	12	Red	38	Flood	4 000	200
55067	H50MR16/FL/Y/CG/4M/GX5.3/12V/STD	50	GX5.3	12	Yellow	38	Flood	4 000	200

COOL BEAM REFLECTOR LAMPS have a dichroic coating that allows for the heat to be released through the back of the lamp; resulting in lower temperature in front of the lamp.

Cool Beam lamps are ideal for restaurants and other heat sensitive environments.

PAR30



PAR38



Order code	Description	Watts (W)	Base	Volts (V)	Colour temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Average life (hrs)	Initial lumens (lm)	Case qty
PAR30											
MOL : 3 23/32 in. (93 mm) Dia. : 3 3/4 in. (95 mm)											
¹ 10145	H75PAR30/CLB/5M/130V/STD	75	E26	130	2 800	40	Flood	1 700	5 000	1 100	15
PAR38											
MOL : 5 9/16 in. (135 mm) Dia. : 4 3/4 in. (121 mm)											
¹ 10146	H60PAR38/CLB/5M/MS/130V/STD	60	E26SKT	130	2 900	36	Flood	1 700	5 000	800	15
¹ 51180	H90PAR38/CLB/5M/MS/130V/STD	90	E26SKT	130	2 900	36	Flood	3 000	5 000	1 140	15

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.



Coloured & Cool Beam Lamps