



Ceramic Metal Halide Lamps

EYE CERA ARC™

Natural Red

Features and Benefits

- The richest "Red" colour rendering in a ceramic metal halide
- Enhances reds creating brilliant, more accurate displays
- Enhances greens, blues and whites with greater accuracy
- True red rendering: R9 up to 90
- High CRI up to 92
- Reduces UV by 90%

Applications

- Meat, fish and produce displays
- Floral displays
- Fine clothing displays
- Jewellery displays

T4.5



Dia. = 0.59 in. (15 mm)
MOL = 3.35 in. (85 mm)
LCL = 2.05 in. (52 mm)

T6 (35 W-70 W)



Dia. = 0.79 in. (20 mm)
MOL = 4.06 in. (103 mm)
LCL = 2.21 in. (56 mm)

T6 (150 W)



Dia. = 0.79 in. (20 mm)
MOL = 4.33 in. (110 mm)
LCL = 2.21 in. (56 mm)

PAR36



Dia. = 4.33 in. (110 mm)
MOL = 4.02 in. (102 mm)

Order Code	Description	Watts (W)	Base	Colour Temp. (K)	ANSI code	CRI	R9	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty
------------	-------------	-----------	------	------------------	-----------	-----	----	--------------------	---------------------	------------------	-----------	--------	-----------	----------

T4.5

60063	CMT35/U/NR936/G8.5 EYE	35	G8.5	3 600	M130	90	90	12 000	7 400	6 100	U	Clear	Enclosed	24
-------	------------------------	----	------	-------	------	----	----	--------	-------	-------	---	-------	----------	----

T6

60062	CMT35/U/NR936/G12 EYE	35	G12	3 600	M130	90	90	12 000	7 400	6 100	U	Clear	Enclosed	24
58128	CMT70/U/NR936/G12 EYE	70	G12	3 600	M139	92	90	12 000	6 600	5 400	U	Clear	Enclosed	24
58124	CMT150/U/NR936/G12 EYE	150	G12	3 600	M142	90	90	12 000	12 000	9 400	U	Clear	Enclosed	24

Order Code	Description	Watts (W)	Base	Colour Temp. (K)	ANSI code	CRI	R9	Average life (hrs)	Initial lumens (lm)	CBCP	Beam Angle (°)	Burn pos.	Luminaire	Case qty
------------	-------------	-----------	------	------------------	-----------	-----	----	--------------------	---------------------	------	----------------	-----------	-----------	----------

PAR36

58139	CM70P36F/U/NR936/MED EYE	70	E26	3 600	M139	90	90	12 000	4 100	2 000	70 x 75	U	Open	24
-------	--------------------------	----	-----	-------	------	----	----	--------	-------	-------	---------	---	------	----