

TRADITIONAL



Traditional

Applications

- Floodlighting
- Warehouse
- Parking garage

ED17



Dia. = 2 1/8 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

ED17



Dia. = 2 1/8 in. (54 mm)
MOL = 5 7/8 in. (138 mm)
LCL = 3 3/8 in. (86 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 3/4 in. (211 mm)
LCL = 5 in. (127 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 3/4 in. (211 mm)
LCL = 5 in. (127 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 3/4 in. (211 mm)
LCL = 5 in. (127 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 3/4 in. (211 mm)
LCL = 5 in. (127 mm)

ED28



Dia. = 3 1/2 in. (89 mm)
MOL = 8 3/4 in. (211 mm)
LCL = 5 in. (127 mm)

O = Open rated for indoor fixtures E = Enclosed rated

Order code	Description	Shape	Base	ANSI code	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty	Figure
------------	-------------	-------	------	-----------	------------------	-----	--------------------	---------------------	------------------	-----------	--------	-----------	----------	--------

175 watts

58041	MH175W/U/MED STD	ED17	E26	M57/E	4 000	65	10 000	14 000	9 100	U	Clear	E	12	A
57979	MH175W/C/U/MED STD	ED17	E26	M57/E	3 700	70	10 000	13 300	8 600	U	Coated	E	12	B
58010	MH175W/U STD	ED28	E39	M57/E	4 000	65	10 000	14 000	9 100	U	Clear	E	12	N
58022	MH175W/C/U STD	ED28	E39	M57/E	3 700	70	10 000	13 300	8 600	U	Coated	E	12	F

250 watts

57978	MH250W/U STD	ED28	E39	M58/E	4 000	65	10 000	21 000	13 700	U	Clear	E	12	N
58078	MPI250W/BU STD	ED28	EX39	M58/O	4 000	65	10 000	21 800	14 200	BU±15°	Clear	O	12	H
58080	MPI250W/C/BU STD	ED28	EX39	M58/O	3 700	70	10 000	20 700	13 500	BU±15°	Coated	O	12	G
57977	MH250W/C/U STD	ED28	E39	M58/E	3 700	70	10 000	20 000	13 000	U	Coated	E	12	F
58047	MS250W/C/BU/3K STD	ED28	E39	M58/E	3 200	70	10 000	20 000	13 000	BU±15°	Coated	E	12	F
58017	MS250W/HOR STD	ED28	EP39	M58/E	4 000	65	10 000	23 000	15 000	HOR±45°	Clear	E	12	O
58061	MH250W/U/T15 STD	T15	E39	M58/E	4 000	65	10 000	21 000	13 700	U	Clear	E	12	P
58074	MS250W/HOR/T15/3K STD	T15	EP39	M58/E	3 200	65	10 000	21 000	13 700	HOR±45°	Clear	E	12	P
58002	MS250W/HOR/T15 STD	T15	EP39	M58/E	4 000	65	10 000	23 000	15 000	HOR±45°	Clear	E	12	P