

The **20 000 HOUR SERIES** is another alternative by STANDARD for an eco-friendly lighting solution. These lamps feature an exceptionally strong multi-support filament construction, which withstands heat, vibration and power surges. Due to a built-in heat shield the heat is kept away from the base, ensuring longer lamp life.

A15



A19



A21



A23



BR30



BR38



ER30



G25



G40



G40



R20



S14



Long Life Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Lumens (lm)	Case qty
A15									
MOL : 3 1/2 in. (89 mm) LCL : 3 1/32 in. (77 mm)									
10263	30A15/CL/20M/120V/STD	30	E26	120	Clear	20 000	C-9/4	175	120
14615	30A15/F/20M/120V	30	E26	120	Frost	20 000	C-11	175	120
A19									
MOL : 4 1/4 in. (108 mm) LCL : 3 1/32 in. (77 mm)									
51121	25A19/CL/20M/120V/STD	25	E26	120	Clear	20 000	C-9/4	105	120
10160	25A19/F/20M/120V/STD	25	E26	120	Frost	20 000	C-9/4	105	120
10161	40A19/CL/20M/120V/STD	40	E26	120	Clear	20 000	C-9/4	200	24
10162	40A19/F/20M/120V/STD	40	E26	120	Frost	20 000	C-9/4	200	120
[†] 10163	60A19/CL/20M/120V/STD	60	E26	120	Clear	20 000	C-9/5	440	24
[†] 10165	100A19/CL/20M/120V/STD	100	E26	120	Clear	20 000	C-9/5	800	120
[†] 10166	100A19/F/20M/120V/STD	100	E26	120	Frost	20 000	C-9/5	800	24
A21									
MOL : 5 3/16 in. (135 mm) LCL : 3 1/2 in. (89 mm)									
[†] 10327	100A21/F/20M/120V/STD	100	E26	120	Frost	20 000	C-9/5	800	24
[†] 10264	150A21/CL/20M/120V/STD	150	E26	120	Clear	20 000	C-9/5	1 300	24
[†] 10265	150A21/F/20M/120V/STD	150	E26	120	Frost	20 000	C-9/5	1 300	24
A23									
MOL : 6 3/16 in. (157 mm) LCL : 5 1/32 in. (128 mm)									
[†] 10262	200A23/F/20M/120V/STD	200	E26	120	Frost	20 000	C-9/5	1 860	24
BR30									
MOL : 5 1/2 in. (130 mm) LCL : 3 3/32 in. (101 mm)									
59235	65BR30/FL/20M/120V/STD	65	E26	120	Clear	20 000	C-9/5	340	60
BR38									
MOL : 5 25/32 in. (147 mm) LCL : 3 9/32 in. (83 mm)									
[†] 10260	75BR38/FL/20M/120V/STD	75	E26	120	Clear	20 000	C-9/5	400	12
[†] 59233	120BR38/FL/20M/120V/STD	120	E26	120	Clear	20 000	CC-9/3	960	24
ER30									
MOL : 6 1/4 in. (159 mm) LCL : 3 1/8 in. (79 mm)									
[†] 14609	50ER30/SP/20M/120V/STD	50	E26	120	Clear	20 000	C-9/5	450	30
G25									
MOL : 4 1/2 in. (114 mm) LCL : 2 7/8 in. (73 mm)									
14598	40G25/CL/20M/120V	40	E26	120	Clear	20 000	C-11	320	60
14600	40G25/WH/20M/120V	40	E26	120	White	20 000	C-11	320	60
G40									
MOL : 6 15/16 in. (176 mm) LCL : 4 3/8 in. (111 mm)									
14606	25G40/CL/20M/120V	25	E26	120	Clear	20 000	C-11	190	24
14605	40G40/WH/20M/120V/STD	40	E26	120	White	20 000	C-9/5	320	24
R20									
MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)									
[†] 10256	50R20/SP/20M/120V/STD	50	E26	120	Clear	20 000	C-9/5	400	200
S14									
MOL : 3 1/2 in. (89 mm) LCL : 2 17/32 in. (64 mm)									
10259	10S14/CL/20M/120V/STD	10	E26	120	Clear	20 000	C-9/5	50	120
14608	11S14/F/20M/120V	11	E26	120	Frost	20 000	C-11	70	120
14613	15S14/CL/20M/120V	15	E26	120	Clear	20 000	C-11	88	120

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Lumens (lm)	Case qty
G40									
MOL : 7 in. (178 mm) LCL : 4 3/8 in. (111 mm)									
52131	5G40/CL/10M/120V/STD	5	E26	120	Clear	10 000	C-2F	9	36
A19									
MOL : 4 1/4 in. (108 mm) LCL : 3 1/32 in. (77 mm)									
[†] 10149	40A19/F/10M/120V/STD/2P (2 pack)	40	E26	120	Frost	10 000	C-9/5	230	24
[†] 10150	60A19/CL/10M/120V/STD/2P (2 pack)	60	E26	120	Clear	10 000	C-9/5	480	24
[†] 10151	60A19/F/10M/120V/STD/2P (2 pack)	60	E26	120	Frost	10 000	C-9/5	480	24

[†] This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.