

Flood

Flood luminaires are designed for use in difficult to reach areas that typically house traditional energy consuming fixtures. They are perfect for a variety of applications such as wall washing, lighting pathways, landscape or signage lighting.

- Durable die cast aluminium heat sink
- Available in bronze, white and black in smaller flood options
- Corrosion resistant stainless steel bolts and screws



Flood Light with Knuckle



80-100 Watts Flood Light with Slip Fitter



120-200 Watts Flood Light with Slip Fitter



Order code	Description	Watts (W)	Volts (VAC)	Colour temp. (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)	Traditionnal equivalent (MH) (HPS)	
Flood Light with Knuckle										
63323	LED/FL/10W/30K/KN/120-277V/BRZ/STD	10	120-277	3 000	>70	50 000	900	120	50W	-
64217	LED/FL/10W/30K/KN/120-277V/WH/STD	10	120-277	3 000	>70	50 000	900	120	50W	-
64218	LED/FL/10W/30K/KN/120-277V/BLK/STD	10	120-277	3 000	>70	50 000	900	120	50W	-
63324	LED/FL/10W/40K/KN/120-277V/BRZ/STD	10	120-277	4 000	>70	50 000	900	120	50W	-
64219	LED/FL/10W/40K/KN/120-277V/WH/STD	10	120-277	4 000	>70	50 000	900	120	50W	-
64220	LED/FL/10W/40K/KN/120-277V/BLK/STD	10	120-277	4 000	>70	50 000	900	120	50W	-
63325	LED/FL/30W/30K/KN/120-277/BRZ/STD	30	120-277	3 000	>70	50 000	2 100	120	70W	70W
63326	LED/FL/30W/40K/KN/120-277/BRZ/STD	30	120-277	4 000	>70	50 000	2 100	120	70W	70W
63327	LED/FL/50W/40K/KN/120-277/BRZ/STD	50	120-277	4 000	>70	50 000	3 700	120	100W	100W
Flood Light with Slip Fitter										
63328	LED/FL/80W/40K/SF/120-277/BRZ/STD	80	120-277	4 000	>70	50 000	6 200	120	175W	150W
63329	LED/FL/100W/40K/SF/120-277/BRZ/STD	100	120-277	4 000	>70	50 000	7 800	120	175W	150W
63337	LED/FL/120W/40K/SF/120-277/BRZ/STD	120	120-277	4 000	>70	50 000	10 000	120	250W	200W
63338	LED/FL/160W/40K/SF/120-277/BRZ/STD	160	120-277	4 000	>70	50 000	14 200	120	400W	250W
63339	LED/FL/200W/40K/SF/120-277/BRZ/STD	200	120-277	4 000	>70	50 000	16 500	120	400W	400W

Weather Proof Cover Plate



Order code	Description	Housing finish colour	Compatible with
Weather Proof Cover Plate *			
64150	KN/ACC/WPCOVER/BRZ/STD	Bronze	63323, 63324, 63325, 63326, 63327
64208	KN/ACC/WPCOVER/WH/STD	White	64217, 64219
64209	KN/ACC/WPCOVER/BLK/STD	Black	64218, 64220

*2 screws (1/24") and foam plate included with weather proof cover plate



Flood and Yard Light



Flood and Yard Light luminaires are designed for use in difficult to reach areas that typically house traditional energy consuming luminaires. These higher power luminaires are perfect for commercial and industrial applications.

- Durable die cast aluminium heat sink
- Corrosion resistant stainless steel bolts and screws
- The Yard Light comes equipped with a dusk to dawn photocell

30-50 Watts
Flood Light
with Yoke



80-100 Watts
Flood Light
with Yoke



Flood Light
with Trunnion



Yard Light



Order code	Description	Watts (W)	Volts (VAC)	Colour temp. (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)	Traditionnal equivalent (MH) (HPS)	
Flood Light with Yoke										
63330	LED/FL/30W/40K/YK/120-277/BRZ/STD	30	120-277	4 000	>70	50 000	2 100	120	70W	70W
63331	LED/FL/50W/40K/YK/120-277/BRZ/STD	50	120-277	4 000	>70	50 000	3 700	120	100W	100W
63332	LED/FL/80W/40K/YK/120/277/BRZ/STD	80	120-277	4 000	>70	50 000	6 200	120	175W	150W
63333	LED/FL/100W/40K/YK/120/277/BRZ/STD	100	120-277	4 000	>70	50 000	7 800	120	175W	150W
Flood Light with Trunnion										
63334	LED/FL/120W/40K/TM/120-277/BRZ/STD	120	120-277	4 000	>70	50 000	10 000	120	250W	200W
63335	LED/FL/160W/40K/TM/120-277/BRZ/STD	160	120-277	4 000	>70	50 000	14 200	120	400W	250W
63336	LED/FL/200W/40K/TM/120-277/BRZ/STD	200	120-277	4 000	>70	50 000	16 500	120	400W	400W
Yard Light *										
63340	LED/YL/35W/40K/120-277/SLV/STD	35	120-277	4 000	>70	50 000	2 500	120	70W	70W
63341	LED/YL/50W/40K/120-277/SLV/STD	50	120-277	4 000	>70	50 000	4 200	120	100W	100W

*CAUTION: This product uses an input 100-277 VAC driver, the actual working voltage is dependent on the input voltage of the photocell that is installed on the product (where applicable).

