



Ambiance

Choose from clear and frost

Style and Savings

\$149.64 per fixture saved on energy and maintenance

Long Life

Lasts 8 times longer than an incandescent

General Purpose



Omni LED lamps deliver crisp and even lighting, creating a comfortable, pleasing atmosphere while offering energy efficacy. Lighting throughout residential and commercial applications.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
A19 Omni ♦♦												
MOL : 4 1/2 in. (110 mm) Dia. : 2 3/8 in. (60 mm)												
63258	LED/OMNI/6.8W/27K/STD	6.8	E26	120	2 700	Frost	80	40 000	450	40	Y	24
63259	LED/OMNI/6.8W/30K/STD	6.8	E26	120	3 000	Frost	80	40 000	450	40	Y	24
63260	LED/OMNI/6.8W/40K/STD	6.8	E26	120	4 000	Frost	80	40 000	480	40	Y	24
63261	LED/OMNI/6.8W/50K/STD	6.8	E26	120	5 000	Frost	80	40 000	480	40	Y	24
63042	LED/OMNI/7W/27K/STD	7	E26	120	2 700	Frost	80	40 000	480	40	Y	12
63043	LED/OMNI/7W/30K/STD	7	E26	120	3 000	Frost	80	40 000	480	40	Y	12
63040	LED/OMNI/9.5W/27K/STD	9.5	E26	120	2 700	Frost	80	40 000	800	60	Y	12
63254	LED/OMNI/9.5W/27K/STD	9.5	E26	120	2 700	Frost	80	40 000	800	60	Y	24
63255	LED/OMNI/9.5W/30K/STD	9.5	E26	120	3 000	Frost	80	40 000	810	60	Y	24
63041	LED/OMNI/9.5W/30K/STD	9.5	E26	120	3 000	Frost	80	40 000	800	60	Y	12
63256	LED/OMNI/9.5W/40K/STD	9.5	E26	120	4 000	Frost	80	40 000	820	60	Y	24
63257	LED/OMNI/9.5W/50K/STD	9.5	E26	120	5 000	Frost	80	40 000	820	60	Y	24
63267*	LED/OMNI/10.5W/27K/ND/STD	10.5	E26	120	2 700	Frost	80	40 000	1 100	75	N	24
GU24 ♦♦												
MOL : 4 1/2 in. (114 mm) Dia. : 2 3/8 in. (60 mm)												
63266	LED/OMNI/9.5W/27K/GU24/STD	9.5	GU24	120	2 700	Frost	80	40 000	800	60	Y	24
A21 Omni ♦												
MOL : 5 3/32 in. (134 mm) Dia. : 2 3/8 in. (60 mm)												
63268	LED/A21/14.5W/27K/ND/STD	14.5	E26	120	2 700	Frost	80	25 000	1 500	100	N	24



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 5 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com